

SYNTHETIC BAG FILTER



Applications:

Capturing fine particles
Second or final stage filter in HVAC
Pre-filter for HEPA filters

Highlights:

- Middle support prevents bypass between filter pockets
- Any special dimensions

Filter Standard:	ISO 16890	Rec. Final Pressure Drop EN13053:	Initial ΔP +100 Pa or initial $\Delta P \times 3$ whichever is lower
Filter Class:	ISO ePM1 - ISO ePM2,5 - ISO ePM10	Max. Operating Temperature:	80°C
Media:	Synthetic Fiber	Frame depth:	20 - 25 mm
Frame:	Galvanized		

SYNTHETIC BAG FILTER

Filter Model	Filter Class		Dimensions WxHxD (mm)	Pocket Number	Filtration Area (m ²)
	EN 779 (cancelled)	ISO16890			
FB-M5-P3-25-287-592-360	M5	Coarse 85%	287x592x360	3	1,5
FB-M5-P4-25-287-592-360	M5	Coarse 85%	287x592x360	4	2
FB-M5-P5-25-490-592-360	M5	Coarse 85%	490x592x360	5	2,5
FB-M5-P6-25-592-592-360	M5	Coarse 85%	592x592x360	6	3
FB-M5-P8-25-592-592-360	M5	Coarse 85%	592x592x360	8	4
FB-M5-P3-25-287-592-500	M5	Coarse 85%	287x592x500	3	2
FB-M5-P4-25-287-592-500	M5	Coarse 85%	287x592x500	4	2,7
FB-M5-P5-25-490-592-500	M5	Coarse 85%	490x592x500	5	3,4
FB-M5-P6-25-592-592-500	M5	Coarse 85%	592x592x500	6	4
FB-M5-P8-25-592-592-500	M5	Coarse 85%	592x592x500	8	5,5
FB-M5-P3-25-287-592-600	M5	Coarse 85%	287x592x600	3	2,4
FB-M5-P4-25-287-592-600	M5	Coarse 85%	287x592x600	4	3,2
FB-M5-P5-25-490-592-600	M5	Coarse 85%	490x592x600	5	4
FB-M5-P6-25-592-592-600	M5	Coarse 85%	592x592x600	6	4,8
FB-M5-P8-25-592-592-600	M5	Coarse 85%	592x592x600	8	6,4
FB-M6-P3-25-287-592-360	M6	ePM10 70%	287x592x360	3	1,5
FB-M6-P4-25-287-592-360	M6	ePM10 70%	287x592x360	4	2
FB-M6-P5-25-490-592-360	M6	ePM10 70%	490x592x360	5	2,5
FB-M6-P6-25-592-592-360	M6	ePM10 70%	592x592x360	6	3
FB-M6-P8-25-592-592-360	M6	ePM10 70%	592x592x360	8	4
FB-M6-P3-25-287-592-500	M6	ePM10 70%	287x592x500	3	2
FB-M6-P4-25-287-592-500	M6	ePM10 70%	287x592x500	4	2,7
FB-M6-P5-25-490-592-500	M6	ePM10 70%	490x592x500	5	3,4
FB-M6-P6-25-592-592-500	M6	ePM10 70%	592x592x500	6	4
FB-M6-P8-25-592-592-500	M6	ePM10 70%	592x592x500	8	5,5
FB-M6-P3-25-287-592-600	M6	ePM10 70%	287x592x600	3	2,4
FB-M6-P4-25-287-592-600	M6	ePM10 70%	287x592x600	4	3,2
FB-M6-P5-25-490-592-600	M6	ePM10 70%	490x592x600	5	4
FB-M6-P6-25-592-592-600	M6	ePM10 70%	592x592x600	6	4,8
FB-M6-P8-25-592-592-600	M6	ePM10 70%	592x592x600	8	6,4

SYNTHETIC BAG FILTER CODE CONFIGURATION

Filter Type	Filter Class	Pocket Number	Flange	Dimensions (mm)
FB : Synthetic Bag Filter	M5 M6 F7 F8 F9	P3 P4 P5 P6 P7 P8 P9 P10 P11 P12	20, 25	592x592x360

SYNTHETIC BAG FILTER

Filter Model	Filter Class		Dimensions WxHxD (mm)	Pocket Number	Filtration Area (m ²)
	EN 779 (cancelled)	ISO16890			
FB-F7-P4-25-287-592-360	F7	ePM2,5 60%	287x592x360	4	2
FB-F7-P6-25-490-592-360	F7	ePM2,5 60%	490x592x360	6	3
FB-F7-P8-25-592-592-360	F7	ePM2,5 60%	592x592x360	8	4
FB-F7-P4-25-287-592-500	F7	ePM2,5 60%	287x592x500	4	2,7
FB-F7-P6-25-490-592-500	F7	ePM2,5 60%	490x592x500	6	4
FB-F7-P8-25-592-592-500	F7	ePM2,5 60%	592x592x500	8	5,5
FB-F7-P4-25-287-592-600	F7	ePM2,5 60%	287x592x600	4	3,2
FB-F7-P6-25-490-592-600	F7	ePM2,5 60%	490x592x600	6	4,8
FB-F7-P8-25-592-592-600	F7	ePM2,5 60%	592x592x600	8	6,4
FB-F8-P4-25-287-592-360	F8	ePM2,5 75%	287x592x360	4	2
FB-F8-P6-25-490-592-360	F8	ePM2,5 75%	490x592x360	6	3
FB-F8-P8-25-592-592-360	F8	ePM2,5 75%	592x592x360	8	4
FB-F8-P4-25-287-592-500	F8	ePM2,5 75%	287x592x500	4	2,7
FB-F8-P6-25-490-592-500	F8	ePM2,5 75%	490x592x500	6	4
FB-F8-P8-25-592-592-500	F8	ePM2,5 75%	592x592x500	8	5,5
FB-F8-P4-25-287-592-600	F8	ePM2,5 75%	287x592x600	4	3,2
FB-F8-P6-25-490-592-600	F8	ePM2,5 75%	490x592x600	6	4,8
FB-F8-P8-25-592-592-600	F8	ePM2,5 75%	592x592x600	8	6,4
FB-F9-P4-25-287-592-360	F9	ePM2,5 85%	287x592x360	4	2
FB-F9-P6-25-490-592-360	F9	ePM2,5 85%	490x592x360	6	3
FB-F9-P8-25-592-592-360	F9	ePM2,5 85%	592x592x360	8	4
FB-F9-P4-25-287-592-500	F9	ePM2,5 85%	287x592x500	4	2,7
FB-F9-P6-25-490-592-500	F9	ePM2,5 85%	490x592x500	6	4
FB-F9-P8-25-592-592-500	F9	ePM2,5 85%	592x592x500	8	5,5
FB-F9-P4-25-287-592-600	F9	ePM2,5 85%	287x592x600	4	3,2
FB-F9-P6-25-490-592-600	F9	ePM2,5 85%	490x592x600	6	4,8
FB-F9-P8-25-592-592-600	F9	ePM2,5 85%	592x592x600	8	6,4