

SYNTHETIC FRAME ZIG-ZAG FILTER

(METAL FREE)



Applications:

Pre-filter for ventilation equipment and HVAC
Highly effective with coarse dust

Highlights:

- Robust construction with synthetic frame
- Highly resistant to moisture
- Disposable
- Simple and light weight
- Higher filtration area
- Energy efficient
- Longer lifespan with high holding capacity
- Hot-melt reinforced pleats

Filter Standard:	ISO 16890	Rec. Final Pressure Drop EN13053:	Initial ΔP +50 Pa or initial ΔP x3 whichever is lower
Filter Class:	ISO Coarse	Max. Operating Temperature:	80°C
Media:	Synthetic Fiber	Standard depth:	48 - 96mm
Frame:	Synthetic		

Filter Model	Filter Class		Dimensions WxHxD (mm)	Filtration Area (m ²)	Nominal Airflow (m ³ /h)	Initial Pressure Drop (Pa)
	EN 779 (cancelled)	ISO 16890				
GZ-G4-S-H-287-287-48	G4	Coarse 65%	287x287x48	0,3	850	75
GZ-G4-S-H-287-592-48	G4	Coarse 65%	287x592x48	0,6	1700	75
GZ-G4-S-H-490-592-48	G4	Coarse 65%	490x592x48	0,9	2600	75
GZ-G4-S-H-592-592-48	G4	Coarse 65%	592x592x48	1,2	3400	75

"Other dimensions are available on request."
 "Differential Pressure Tolerance (±10% + 5 Pa) or (10 Pa + 5 Pa) whichever is greater"

SYNTHETIC FRAME ZIG-ZAG FILTER (METAL FREE) CODE CONFIGURATION

Filter Type	Filter Class	Media	Capacity	Dimensions (mm)
GZ-S-H : Synthetic Frame Zig-Zag Filter (Metal Free)	G4	S : Synthetic	H: High	592x592x48

