

ULPA CEILING FILTER

(ALUMINIUM FRAME)



Applications:

Final filter for cleanrooms
Microelectronics

Highlights:

- High quality glass fiber media
- Guaranteed leak free
- Individual test certificate (acc. to EN 1822 - ISO 29463)
- Optimized velocity distribution
- Suitable for HEPA Boxes and Cabinets

Filter Standard:	EN 1822 and ISO 29463	Max. Operating Temperature:	80°C
Filter Class:	U15 - U16 - U17	Faceguard:	Aluminium sheet (powder coated)
Media:	High quality glass fiber	Gasket:	EPDM flat, EPDM flat continous and PU foam
Frame:	Anodized extruded aluminium	Sealing Compound:	Two component polyurethane
Rec. Final Pressure Drop:	Initial pressure drop x2, (max. 600 Pa)	Seperator:	Hotmelt

Filter Model	Filter Class		Dimensions WxHxD (mm)	Filtration Area (m ²)	Pleat Height (mm)	Nominal Airflow (m ³ /h)	Initial Pressure Drop (Pa)
	EN 1822	ISO 29463					
UC-U15-A-1-305-305-69-FB-P	U15	ISO 55 U	305x305x69	2,5	50	150	140
UC-U15-A-1-305-610-69-FB-P	U15	ISO 55 U	305x610x69	5	50	300	140
UC-U15-A-1-457-457-69-FB-P	U15	ISO 55 U	457x457x69	5,6	50	340	140
UC-U15-A-1-610-610-69-FB-P	U15	ISO 55 U	610x610x69	10	50	600	140
UC-U15-A-1-610-915-69-FB-P	U15	ISO 55 U	610x915x69	15	50	900	140
UC-U15-A-1-610-1220-69-FB-P	U15	ISO 55 U	610x1220x69	20	50	1200	140
UC-U15-A-1-762-915-69-FB-P	U15	ISO 55 U	762x915x69	18,8	50	1130	140
UC-U15-A-1-915-915-69-FB-P	U15	ISO 55 U	915x915x69	22,5	50	1350	140
UC-U15-A-1-610-1525-69-FB-P	U15	ISO 55 U	610x1525x69	25	50	1500	140
UC-U15-A-1-610-1830-69-FB-P	U15	ISO 55 U	610x1830x69	30	50	1800	140

"Other dimensions are available on request."
"Differential Pressure Tolerance ±10%"

ULPA CEILING FILTER (ALUMINIUM FRAME) CODE CONFIGURATION

Filter Type	Filter Class	Frame	Pleat Height	Dimensions (mm)	Faceguard	Gasket
UC : ULPA Ceiling Filter Aluminium Frame	U15	A: Aluminium	1: 50 mm 2: 65 mm 3: 75 mm 4: 85 mm 5: 90 mm 6: 100 mm 7: 125 mm	610x610x69	FW: Without FC: On Clean Side FD: On Dirty Side FB: On Both Sides	W: Without P: Continuous Pu Foam PP: Pu Foam on Both Side E: EPDM Flat EE: EPDM Flat on Both Side C: Continuous Grey EPDM CC: Grey EPDM on Both Side U: U Gasket

