

HVAC MODEL V-COMPACT FILTER



Applications:

Capturing fine particles
Second or final stage filter in HVAC
Pre-filter for HEPA filters

Highlights:

- Eurovent certified
- Large filtration area
- Simple and light weight
- High dust holding capacity
- Low initial pressure drop

Filter Standard:	ISO 16890	Max. Operating Temperature:	80°C
Filter Class:	ISO ePM1- ISO ePM2,5 - ISO ePM10	Faceguard:	Available on request
Media:	Glass Fiber	Gasket:	Available on request
Frame:	Polystyrene (PS)	Sealing Compound:	Two component polyurethane
Rec. Final Pressure Drop EN13053:	Initial ΔP +100 Pa or initial ΔP x3 whichever is lower	Separators:	Hotmelt

Filter Model	Filter Class		Filtration Area (m ²)	Nominal Airflow (m ³ /h)	N. Initial Pressure Drop (Pa)	Rated Airflow (m ³ /h)	R. Initial Pressure Drop (Pa)	Energy Class
	EN 779 (cancelled)	ISO 16890						
FV-M6-287-592-292-FW-W	M6	ePM10 75%	7	2125	108	1700	80	E
FV-M6-490-592-292-FW-W	M6	ePM10 75%	11,5	3500	108	2700	80	E
FV-M6-592-592-292-FW-W	M6	ePM10 75%	14	4250	108	3400	80	E
FV-F7-287-592-292-FW-W	F7	ePM1 55%	7	2125	130	1700	90	D
FV-F7-490-592-292-FW-W	F7	ePM1 55%	11,5	3500	130	2700	90	D
FV-F7-592-592-292-FW-W	F7	ePM1 55%	14	4250	130	3400	90	D
FV-F8-287-592-292-FW-W	F8	ePM1 75%	7	2125	150	1700	100	C
FV-F8-490-592-292-FW-W	F8	ePM1 75%	11,5	3500	150	2700	100	C
FV-F8-592-592-292-FW-W	F8	ePM1 75%	14	4250	150	3400	100	C
FV-F9-287-592-292-FW-W	F9	ePM1 80%	7	2125	185	1700	120	D
FV-F9-490-592-292-FW-W	F9	ePM1 80%	11,5	3500	185	2700	120	D
FV-F9-592-592-292-FW-W	F9	ePM1 80%	14	4250	185	3400	120	D

"Other dimensions are available on request."

"Differential Pressure Tolerance (±10% + 5 Pa) or (10 Pa + 5 Pa) whichever is greater"

HVAC MODEL V-COMPACT FILTER CODE CONFIGURATION

Filter Type	Filter Class	Dimensions (mm)	Faceguard	Gasket
FV : HVAC Model V-Compact Filter	M6 F7 F8 F9	592x592x292	FW : Without FC2: On 2 Edge Sides FC8: On 8 Edge Sides	W: Without P: Continuous Pu Foam PP: Pu Foam on Both Sides E: EPDM EE: EPDM Flat On Both Sides

